

Specifications

System

Model IQKeySafe-400

Cabinet Type Safe

Cabinet certification
SS3492 (Swedish Standard)

Storage capacity

- Minimum 10 keys in the door
- Minimum 30 keys in the cabinet
- Maximum 70 keys in the door
- Maximum 330 keys in the cabinet

Keymodule extensions

- 10-keys module

Location of computer module

Built into the door

Computer module

Industrial PC, Intel Atom 1.6 GHz,
Built-in HDD/SSD and CF Card,
1GB RAM, 8.9" Touch-screen,
2 Ethernet interface, RS232, USB,
Windows XP Embedded.

Mechanical & Environmental data

Physical dimensions (width x height x depth)

700mm x 1500mm x 600mm

Power Requirement

230V 50Hz AC

Internal Battery

7Ah, up to 1.5 hour operation

Consumption

60W

Operating Temperature

0 - 40°C

Color of the Cabinet

RAL 9002

Security

Card reader

- USB / RS232
- Mifare 13.56 MHz
- EM 125 KHz

Fingerprint reader (optional)

USB / RS232



Key holder

CleverKey (keyholder with RFID-chip)

Operation

Number of keys to be able to pick up within one login session

10 keys

Remote management

WEB Interface Available

Network Mode

- Cabinets synchronize data with each other
- Local and Central database

Communication with External Systems

- Interface is available for ERP integration
- Based on XML and WEB service

Emergency open

- Max. 10 keys in one time
- Works using emergency key and button
- Enable emergency from external input



LOXTORE AB

Forradsvagen 10, S-141 46 Huddinge, Sweden

Phone: +46 709 500040, +46 8 559 255 39

<http://www.loxtore.com>

