

Specifications

System

Modell IQWallCabinet-80

Cabinet Type Wall Cabinet

Storage capacity

- Minimum 10 keys
- Maximum 80 keys

Keymodule extensions

- 10-keys module

Doors

- Metal door (right sided, left sided)
- Transparent plastic door (right sided, left sided)

Location of computer module

- Left to key modules block
- Right to key modules block

Computer module

Industrial PC, Intel Atom 1.6 GHz,
Built-in HDD/SSD and CF Card,
1GB RAM, 8.9" Touch-screen,
2 Ethernet interface, RS232, USB,
Windows XP Embedded.

Mechanical & Environmental data

Physical dimensions (width x height x depth)

780mm x 875mm x 110mm

Power Requirement

230V 50Hz AC

Internal Battery

7Ah, up to 1.5 hour operation

Consumption

60W

Operating Temperature

0 - 40°C

Color of the Cabinet

- RAL 9002
- on demand

Security

Card reader

- USB / RS232
- Mifare 13.56 MHz
- EM 125 KHz



Fingerprint reader (optional)

USB / RS232

Key holder

CleverKey (keyholder with RFID-chip)

Operation

Number of keys to be able to pick up within one login session

10 keys

Remote management

WEB Interface Available

Network Mode

- Cabinets synchronize data with each other
- Local and Central database

Communication with External Systems

- Interface is available for ERP integration
- Based on XML and WEB service

Emergency open

- Max. 10 keys in one time
- Works using emergency key and button
- Enable emergency from external input



LOXTRE AB

Forradsvagen 10, S-141 46 Huddinge, Sweden

Phone: +46 709 500040, +46 8 559 255 39

<http://www.loxtore.com>

